

MySQL Hoofdpagina

Exporteer alle Databases

```
root@gw-famnet# mysqldump --user=XXXXXXXX --password=XXXXXXXX -A > /PATH/T0/DUMPFIL.E.SQL
```

Exporteer meerdere databases

```
root@gw-famnet# mysqldump --user=XXXXXXXX --password=XXXXXXXX --databases DB_NAME1 DB_NAME2 DB_NAME3 > /PATH/T0/DUMPFIL.E.SQL
```

Exporteer sommige tabellen

```
root@gw-famnet# mysqldump --user=XXXXXXXX --password=XXXXXXXX --databases DB_NAME --tables TABLE_NAME > /PATH/T0/DUMPFIL.E.SQL
```

Exporteer 1 database

Standaard SQL (platte tekst)

```
root@gw-famnet# mysqldump --user=databasegebruikersnaam --password=wachtwoord --databases databasenaam > /PATH/T0/bestandsnaam.sql
```

Als XML bestand (platte tekst)

```
root@gw-famnet# mysqldump --user=databasegebruikersnaam --password=wachtwoord --databases databasenaam --xml > /PATH/T0/bestandsnaam.**xml**
```

Gezipd XML bestand

```
root@gw-famnet# mysqldump --user=databasegebruikersnaam --password=wachtwoord --databases databasenaam --xml | gzip -9 > /PATH/T0/bestandsnaam.gz
```

Create database

```
root@gw-famnet# mysql -u root -p
```

```
mysql> CREATE DATABASE cms;
```

Create database user

Aanmaken van een user met verschillende mogelijkheden

Vanaf version 5.x. :

```
mysql> CREATE USER 'gebruiker'@'localhost IDENTIFIED BY 'wachtwoord';
= inclusief de '
Query OK, 0 rows affected (0.00 sec)
```

Voor ouder 4.x databases:

```
mysql> GRANT ALL PRIVILEGES ON databasenaam.* TO 'gebruiker'@'localhost'
IDENTIFIED BY 'password';
gebruiker mag alles in de tabellen van deze database
Query OK, 0 rows affected (0.02 sec)
```

```
mysql> CREATE USER 'monty'@'%' IDENTIFIED BY 'some_pass';
mysql> GRANT ALL PRIVILEGES ON *.* TO 'monty'@'%' WITH GRANT OPTION; "user
mag alles op elke db en table, incl. toekennen van opties, en dat vanaf elke
machine"
```

see <http://dev.mysql.com/doc/refman/5.1/en/adding-users.html>

Importeer database

```
root@gw-famnet# mysql -u #username# -p #database# < #dump_file#
```

Backup cmsms site

```
tar -czvf cmsms-website.tgz --absolute-names --preserve-permissions --
preserve-order /var/www/cmsms
```

Database naam en user vervangen

CMSMS : in het config.php file

```
#-----
#Database Settings
#-----
```

```
#This is your database connection information. Name of the server,  
#username, password and a database with proper permissions should  
#all be setup before CMS Made Simple is installed.  
$config['dbms'] = 'mysql';  
$config['db_hostname'] = 'localhost';  
$config['db_username'] = 'username';  
$config['db_password'] = 'password';  
$config['db_name'] = 'databasename';  
#Change this param only if you know what you are doing  
$config["db_port"] = '';
```

Wijzig in het MySQL dumpfile.sql

```
\--  
\-- Current Database: `artwam`  
\--  
  
CREATE DATABASE /*!32312 IF NOT EXISTS*/ `artwam` /*!40100 DEFAULT  
CHARACTER SET utf8 */;  
  
USE `artwam`;
```

Backup CMS

[Backup CMS](#)

WordPress Perikelen

[URL problemen in de MySQL database](#)

WordPress Perikelen

`/usr/syno/mysql/bin/mysql -u root`

From:
<https://studie.famvisser.net/> - **Studie Pagina Chavoerah Maqor**

Permanent link:
<https://studie.famvisser.net/doku.php?id=mysql&rev=1430660006>

Last update: **2022/05/06 21:58**

