

shutdown

```
/? - Display help. This is the same as not typing any options.  
/i - Display the graphical user interface (GUI). This must be the first  
option.  
/l - Log off. This cannot be used with /m or /d options.  
/s - Shutdown the computer.  
/r - Shutdown and restart the computer.  
/g - Shutdown and restart the computer. After the system is rebooted,  
restart any registered applications.  
/a - Abort a system shutdown. This can only be used during the time-out  
period.  
/p - Turn off the local computer with no time-out or warning. Can be used  
with /d and /f options.  
/h - Hibernate the local computer. Can be used with the /f option.  
/e - Document the reason for an unexpected shutdown of a computer.  
/m - \\computer Specify the target computer.  
/t xxx - Set the time-out period before shutdown to xxx seconds. The valid  
range is 0-315360000 (10 years), with a default of 30.  
        If the timeout period is greater than 0, the /f parameter is  
implied.  
/c - "comment" Comment on the reason for the restart or shutdown. Maximum of  
512 characters allowed.  
/f - Force running applications to close without forewarning users. The /f  
parameter is implied when a value greater than 0 is specified for the /t  
parameter.  
/d [p|u:]xx:yy - Provide the reason for the restart or shutdown. p indicates  
that the restart or shutdown is planned.  
        u indicates that the reason is user defined. If neither p  
nor u is specified the restart or shutdown is unplanned.
```

From:

<https://studie.famvisser.net/> - **Studie Pagina Chavoerah Maqor**

Permanent link:

https://studie.famvisser.net/doku.php?id=win_shutdown&rev=1396450880

Last update: **2022/05/06 21:58**

