

## shutdown

`/?` - Display help. This is the same as not typing any options.

`/i` - Display the graphical user interface (GUI). This must be the first option.

`/l` - Log off. This cannot be used with `/m` or `/d` options.

`/s` - Shutdown the computer.

`/r` - Shutdown and restart the computer.

`/g` - Shutdown and restart the computer. After the system is rebooted, restart any registered applications.

`/a` - Abort a system shutdown. This can only be used during the time-out period.

`/p` - Turn off the local computer with no time-out or warning. Can be used with `/d` and `/f` options.

`/h` - Hibernate the local computer. Can be used with the `/f` option.

`/e` - Document the reason for an unexpected shutdown of a computer.

`/m` - `\\computer` Specify the target computer.

`/t xxx` - Set the time-out period before shutdown to xxx seconds. The valid range is 0-315360000 (10 years), with a default of 30.

If the timeout period is greater than 0, the `/f` parameter is implied.

`/c` - "comment" Comment on the reason for the restart or shutdown. Maximum of 512 characters allowed.

`/f` - Force running applications to close without forewarning users. The `/f` parameter is implied when a value greater than 0 is specified for the `/t` parameter.

`/d [p|u:]xx:yy` - Provide the reason for the restart or shutdown. `p` indicates that the restart or shutdown is planned.

`u` indicates that the reason is user defined. If neither `p` nor `u` is specified the restart or shutdown is unplanned.

From:

<https://studie.famvisser.net/> - **Studie Pagina Chavoerah Maqor**

Permanent link:

[https://studie.famvisser.net/doku.php?id=win\\_shutdown&rev=1396450880](https://studie.famvisser.net/doku.php?id=win_shutdown&rev=1396450880)

Last update: **2022/05/06 21:58**

